

MECAMAQ HYDRAULIC PRESSES

PHH series



PHH-250 ▲



mecamaq
HYDRAULIC PRESSES



mecamaq

Straightening of beams and structural profiles



PLC control with tactile panel

Special tools and anti-spin system



Hydraulic System assembled inside of press frame



Adjustable height roller track



Features

- ✔ Monoblock frame manufactured with structural steel 5355 (calculated with finite element analysis software).
- ✔ T-Slots "M16" "DIN 650".
- ✔ 2 speeds with automatic change of fast speed by pressure.
- ✔ Limit switches.
- ✔ Pressure regulator.
- ✔ Electric Selector (MANUAL-AUTOMATIC RETURN)
- ✔ Activation by electric pedals.

Series Specifications

PHH Series	PHH-150	PHH-200	PHH-250	PHH-300	PHH-400
Power (tons).	150	200	250	300	400
Stroke (mm)	400	400	400	400	400
Fixed plate (mm)	1500x500	1800x500	2000x550	2000x600	2200x650
Movable plate (mm)	450x400	450x400	500x400	550x450	600x500
Max. opening	700	800	900	1000	1000
Engine power (HP)	5,5	5,5	7,5	10	12,5
Approximation speed (mm/sec)	10	10	10	10	10
Work speed (mm/sec)	2	2,4	2,5	2,6	2,5
Max. pressure (bars)	300	315	310	315	315

Optional Equipment

- ✔ PLC Control with tactile panel (SIEMENS).
- ✔ Adjustable height roller track.
- ✔ Customized dimensions
- ✔ More optional equipment under request.




PHH-250 ▶

- 250Tm.
- Horizontal press
- Fixed plate 2500x500mm.
- Opening 900mm.
- Stroke 400mm.
- Motorized roller track



PHH-180 ▶

- 180Tm.
- Horizontal Press
- Fixed plate 3000x600mm.
- Opening 850mm.
- Stroke 400mm.
- Special position for operator



mecamaq
HYDRAULIC PRESSES

Autovía NII, salida 487-484
Pol. Ind. SAU-3
C/ Bassots, Parcela nº10
25243 El Palau d'Anglesola (Lleida)

Tel. (+34) 973 71 12 81
mecamaq@mecamaq.com
www.mecamaq.com

